

J500 5:1 Air-Operated Oil Pumps

J500 - with 940mm suction tube / J500S - stubby pump

This double acting air operated high-pressure pump is designed for dispensing lubricants in larger installations. Suitable for use with multiple dispensing points with simultaneous operation. Typical fluids handled include, engine oil, synthetic oil, hydraulic oil, transmission fluid, maximum viscosity SAE240. Pumps include height adjustable bung adaptor 2" BSP (M).

FEATURES:

- Precision machined to ensure stability and long life
- Double action
- Easy to operate and maintain
- Suitable for use with antifreeze and oils up to SAE 240
- Supplied with 2" adjustable bung adaptor
- Suitable for use with engine oil, synthetic oil, hydraulic oil, gear oil, automatic transmission fluid and anti-freeze
- Low noise level - quiet efficient and reliable

LubeWORKSTM
Solution for Lubricating Equipment



TECHNICAL DATA

Ratio	5:1
Working pressure	2-10 bar (30-150psi)
Maximum fluid pressure	50 bar (750psi)
Air consumption	@10 bar - 78 L/min
Output capacity ltr./min.	18 L/min
Suction tube diameter mms	42 mm
Air inlet connection	1/4" quick plug
Oil delivery connection	1/2" male
Maximum viscosity	240 SAE
Test media, SAE30 oil @ 20°C through 2mtr hose length free outlet	

Mounting
Brackets &
Accessories
available -
please see
page 125 & 157